Claims:

1. A convertible vehicle (1) with a roof (2) having a roof covering (3) and several lateral frame parts (5; 6; ...), which at least partially span the roof covering (3) when the roof (2) is closed and follow each other in the longitudinal direction of the vehicle, in which a rear frame part (5) extends from a window parapet line (7) with an upward extending component, characterized in that the adjacent frame part (6), preceding the rear frame part (5) in the direction of travel (F) when roof 2 is closed, can be moved without a force transfer through the rear frame part (5) by at least one drive (9) provided for roof opening, and the rear frame part (5) is suspended on a gear mechanism that transfers the drive force and can be moved by it.

5

- A convertible vehicle (1) according to Claim 1, characterized in that the adjacent frame part (6) is connected to a pivot joint (11) along with the rear frame part (5).
- A convertible vehicle (1) according to Claim 1, characterized in that the rear frame part (5) is connected to body (8) through at least one separate movable connection mechanism (12).
- A convertible vehicle (1) according to Claim 3,
 characterized in that the connection mechanism (12) includes two levers (13a; 13b) forming a double joint (13) and connected to each other on a pivot joint (14).
- A convertible vehicle (1) according to Claim 4,
 characterized in that the rear frame part (5) is firmly connected to a lever (13b) of the double joint (13).
- A convertible vehicle (1) according to Claim 1,
 characterized in that the rear frame part (5), in its lower end area (16),
 has no direct body connection, at least during roof movement.

- 7. A convertible vehicle (1) according to Claim 1, characterized in that to transfer force between drive (9) and adjacent frame part (6), a multiple joint (10) engaging on a vehicle body (8) on one end and on an adjacent frame part (6) on the other end, is used.
- A convertible vehicle (1) according to Claim 7,
 characterized in that the multiple joint (10) is a four pivot joint suspension (19; 20; 21, 22).
- 9. A convertible vehicle (1) according to Claim 8,

 characterized in that the four pivot joint suspension (19; 20; 21; 22)
 includes two links (27; 18) mounted on body (8) and extending upward to adjacent frame part (6) and connected so as to pivot there.
 - 10. A movable vehicle roof for a convertible vehicle according to Claim 1.